

# SILICONE SCI 2200



## Application

SCI-2200 has excellent adhesion to: Glass Aluminium, Granit, Painted, Bright Steel, Fiberglass, Stainless, Finihed-woods, Ceramics, Acrylic sheet nd most Plastic.

- Standard and butt glazing : frames, panets, hop fronts
- Curtain wall sealing
- Sealing environmental and refrigerated rooms, sheet metal, skylights, ventilators, air conditioning units, solar collectors, interior glass partitions.
- Assembly of metal/plasic signs
- Drought proofing.

## Packing and Storage

SCI-2200 is available in plastic 310 ml. cartridges. Shelf life is 1 year when stored at or below 25C  
Color : Clear, White, Black, Aluminium.

## Product Characteristics

<b>Cure System</b>	: Axetoxy
<b>Shore A hardness</b>	: Min 20 shore A
<b>Tenslle Strength at rupture</b>	: 1.55 N/mm2
<b>Elongation a break(Min)</b>	: 350%
<b>Movement accommodation</b>	: -25% to + 25%
<b>Full Cure</b>	: 1-3 days
<b>Application temp. range</b>	: -30C to +60C
<b>Tack free time (Max)</b>	: 10 - 20 Min
<b>Service temp. range</b>	: -50C to + 150C
<b>Tooling time</b>	: Approx 6 min.

